

MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION

PRODUCT NAME: **SCRUB 'N SHINE FLOOR REJUVENATOR**
DESCRIPTION: POLYMERIC LIQUID
NPCA HMIS RATING: H 2 F 1 R 0 LAST REVISED : 02/05/2007
DATE OF ISSUE: 04/27/2013
MANUFACTURED FOR: BLUE STAR OF NEW JERSEY, INC.
ADDRESS: 1553 DELSEA DRIVE, DEPTFORD, NJ 08096
CUSTOMER: INFORMATION TELEPHONE: 856-848-4236
24 HOUR RESPONSE NUMBER (CHEMTEL): 1-800-255-3924 (NORTH AMERICA)

We certify that its products comply with all the provisions of the
Toxic Substances Control Act (TSCA), unless otherwise stated by
ingredient in Section II.

*** The percent by weight composition data given in Sections II ***
*** and X are NOT SPECIFICATIONS, but are based on 'target' ***
*** formula values for each ingredient in the product. The data ***
*** are presented as ranges for low hazard ingredients and single ***
*** point values for ingredients of regulatory concern. Actual ***
*** batch concentrations will vary within limits consistent with ***
*** separately established product specifications. ***

SECTION II INGREDIENTS

1
CAS# 000111-77-3
DIETHYLENE GLYCOL METHYL ETHER
PCT BY WT: 3.500 VAPOR PRESSURE: .200 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: NONE ESTABLISHED
OSHA PEL/TWA: NONE ESTABLISHED
LD50, Oral: 7128 MG/KG (MOUSE AND RAT)
LD50, Dermal: 9404 MG/KG (RABBIT)
LC50, Inhalation: >2000 MG/CU.M., 1 HR (RAT)

2
CAS# 000084-74-2
DIBUTYL PHTHALATE
PCT BY WT: 1.75 VAPOR PRESSURE: .100 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 5 MG/CU.M.
OSHA PEL/TWA: 5 MG/CU.M.
LD50, Oral: 8000 MG/KG (RAT)
LD50, Dermal: 20,940 MG/KG (RABBIT)

This substance is classified as a hazardous air pollutant.

This product contains no reported carcinogens or suspected carcinogens.

SECTION III PHYSICAL DATA

Boiling Range: High- -N/A F Low- 212.0 F
Vapor Pressure: See Section II
Theoretical Weight per Gallon, Calculated: 8.7456 LB/GL
Theoretical Specific Gravity, Calculated: 1.051
Theoretical VOC, Calculated: .523 LB/GL
--If applicable, see Section X for further VOC information--
Physical State: LIQUID
Appearance: OFF-WHITE, MILKY
Odor: MILD
Odor Threshold: -N/A
pH: -N/A
Freezing Point: -N/A
Water Solubility: COMPLETELY DISPERSIBLE
Coefficient of Water/Oil Distribution: -N/A
Mechanical Impact Explosion: NO KNOWN HAZARD
Static Electricity Explosion: NO KNOWN HAZARD

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CHARACTERISTICS:
Lowest Closed Cup Flashpoint: 201.0 degrees F
Lower Flammable Limit in Air: Lower- -N/A % by volume
OSHA Flammability Classification: N/A
DOT Flammability Classification: N/A
DOT Shipping Name:
PLASTIC MATERIALS, LIQUID-NOT REGULATED FOR ANY MODE OF TRANSPORTATION
EXTINGUISHING MEDIA:
None required.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
None known.
SPECIAL FIRE FIGHTING PROCEDURES:
None known.
ADDITIONAL TRANSPORTATION INFORMATION:
Freight Classification:
NMFC: 149980/SUB 2 RESIN COMPOUNDS, LIQUID LTL CLASS 55

SECTION V HEALTH HAZARD DATA

EFFECTS OF EXCESSIVE OVEREXPOSURE. PRIMARY ROUTES OF ENTRY ARE:

EYE CONTACT:

Direct contact with product may cause irritation.

SKIN CONTACT:

Prolonged or repeated contact with product may cause mild irritation.

INHALATION:

Prolonged overexposure to vapors or dust in poorly ventilated areas may cause nose and throat irritation.

MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION

PRODUCT NAME: **SCRUB 'N SHINE FLOOR REJUVENATOR**
DESCRIPTION: POLYMERIC LIQUID
NPCA HMIS RATING: H 2 F 1 R 0 LAST REVISED : 02/05/2007
DATE OF ISSUE: 04/27/2013
MANUFACTURED FOR: BLUE STAR OF NEW JERSEY, INC.
ADDRESS: 1553 DELSEA DRIVE, DEPTFORD, NJ 08096
CUSTOMER: INFORMATION TELEPHONE: 856-848-4236
24 HOUR RESPONSE NUMBER (CHEMTEL): 1-800-255-3924 (NORTH AMERICA)

We certify that its products comply with all the provisions of the
Toxic Substances Control Act (TSCA), unless otherwise stated by
ingredient in Section II.

*** The percent by weight composition data given in Sections II ***
*** and X are NOT SPECIFICATIONS, but are based on 'target' ***
*** formula values for each ingredient in the product. The data ***
*** are presented as ranges for low hazard ingredients and single ***
*** point values for ingredients of regulatory concern. Actual ***
*** batch concentrations will vary within limits consistent with ***
*** separately established product specifications. ***

SECTION II INGREDIENTS

1
CAS# 000111-77-3
DIETHYLENE GLYCOL METHYL ETHER
PCT BY WT: 3.500 VAPOR PRESSURE: .200 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: NONE ESTABLISHED
OSHA PEL/TWA: NONE ESTABLISHED
LD50, Oral: 7128 MG/KG (MOUSE AND RAT)
LD50, Dermal: 9404 MG/KG (RABBIT)
LC50, Inhalation: >2000 MG/CU.M., 1 HR (RAT)

2
CAS# 000084-74-2
DIBUTYL PHTHALATE
PCT BY WT: 1.75 VAPOR PRESSURE: .100 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 5 MG/CU.M.
OSHA PEL/TWA: 5 MG/CU.M.
LD50, Oral: 8000 MG/KG (RAT)
LD50, Dermal: 20,940 MG/KG (RABBIT)

This substance is classified as a hazardous air pollutant.

INGESTION:

May cause mouth, throat, esophagus and stomach irritation, nausea, vomiting and diarrhea.

EMERGENCY AND FIRST AID PROCEDURES:

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water while removing contaminated clothing and shoes. Wash contaminated clothing. Thoroughly clean contaminated shoes. If affected by inhalation of vapors or spray mist, remove to fresh air. If swallowed, get medical attention immediately.

CALIFORNIA PROPOSITION 65 INFORMATION:

This material contains no intentionally-added ingredients, covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986" (Proposition 65), unless specifically stated under OTHER HEALTH HAZARDS, by individual chemical.

OTHER HEALTH HAZARDS:

DIETHYLENE GLYCOL MONOMETHYL ETHER (DEGMME)

DEGMME may be harmful if absorbed through the skin. It may cause adverse reproductive effects such as birth defects, miscarriage, or infertility based on animal studies. DEGMME is also a peroxide former.

SECTION VI REACTIVITY DATA

STABILITY: Stable **HAZARDOUS POLYMERIZATION:** None under normal conditions.

CONDITIONS TO AVOID:

Protect from freezing. Do not store at or below 32 degrees F.

Protect from elevated temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID):

None reasonably foreseeable.

HAZARDOUS DECOMPOSITION PRODUCTS:

Incomplete combustion can produce carbon monoxide.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Avoid breathing vapors. Ventilate area. Contain and remove with inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

Avoid breathing of spray mist. If sprayed, wear mechanical filter respirator to remove solid particles of overspray. Follow respirator manufacturer's directions for respirator use.

VENTILATION:

Provide general clean air dilution or local exhaust ventilation in volume and pattern to prevent air contaminant concentration build-up. Refer to OSHA Standard 1910.94.

PROTECTIVE GLOVES:

If there is potential for prolonged or repeated skin contact, wear plastic gloves for the duration of anticipated exposure.

EYE PROTECTION:

Avoid contact with eyes. Use safety eyewear with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT:

None normally required. If unable to avoid prolonged or repeated contact with skin, wear protective clothing.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 100 deg. F. Keep containers closed when not in use and upright to prevent leakage.

OTHER PRECAUTIONS:

Do not take internally. Wash hands after using and before eating.

KEEP OUT OF REACH OF CHILDREN FOR INDUSTRIAL USE ONLY

SECTION X Sara Title III Information

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

DIETHYLENE GLYCOL METHYL ETHER

CAS# 000111-77-3 PCT BY WT: 5.9800

DIBUTYL PHTHALATE

CAS# 000084-74-2 PCT BY WT: 2.9400